



## 3z 2021 SPECIFICATIONS

Length Overall w/ Engines & Bow Roller	37' 11"	Displacement 1/2 Load	13,279 lbs.
Length on Deck	35' 8"	Fuel Capacity	250 gal.
Beam	11"	Water Capacity	58 gal.
Draft (Drives Up/ Down)	21"/32"	Standard Power	Twin 300hp Outboards
Air Height (w/ Radar)	8' 10"		

### HULL & DECK

- Modified deep-V hull w/42 degree cutwater and 19.5-degree deadrise
- Certified ISO Category B Offshore
- Strong, light, modified epoxy infusion cored composite
- Hull painted in Awlcraft 2000 color of choice w/2 clear coats
- Metallic, custom paint and/or added stripes are subject to additional charges
- Cored deck fused to hull as monocoque structure w/solid glass or Penske backing of hardware
- Large 4x5 cockpit hatch
- Starboard cockpit locker
- Port cockpit locker w/refrigerator
- Dual-opening windshields w/wiper & washers
- 316 SS custom deck cleats (6) and chocks (2)
- Exterior and interior safety hand rails
- Retractable swim/safety ladder on outboard platform
- Ultraleather cockpit cushions
- Varnished teak drawers (2) and dual position cabin & pilot-house 24x36 double-leaf table
- Tinted sliding glass side windows
- Roll-up StrataGlass aft w/dual window/screen
- Cockpit sole storage hatch
- Large pilothouse settee lockers & large port, aft settee locker
- 4 overhead hatches, 2 fixed hull ports
- Stidd 500 helm seats on telescoping swivel bases
- 5/8" Rode w/chain, Washdown & Muir Windlass
- 2.5' x 4' national flag w/varnished teak staff

### NAVIGATION

- Anti-glare console w/Ritchie SS-2000 "MJM" compass
- Stainless Dual Trumpet Electric Horn
- Garmin GPSMAP® 8612
- Garmin VHF 215 over Helm
- Mercury Smart Pilot Autopilot
- Mercury Vessel View MFD

### PROPULSION & STEERING

- Twin Mercury Verado 300XLs w/Joystick Piloting, Skyhook and Auto Trim
- 24" Stainless destroyer wheel with teak rim
- Electric Zipwake 450S Interceptor trim tabs
- 250 gallon vented fuel tank

### INTERIOR

- Enclosed head
- Gloss finished teak & wenge sole w/storage locker
- Classic cherry-trimmed off-white panels

### ELECTRICAL

- 12V DC System with breaker switches and digital multimeter
- 120V AC Shorepower System w/Victron 5000W inverter, 50', 30Amp Shorepower cord, 4-GFI/USB duplex outlets with breaker switches and digital multimeter
- Dimmable overhead LED lights on bridge deck & in head
- Courtesy lights (2) and locker lights (4)
- 410-ampere hour battery capacity with 1-4D 200 AH house & 2-Group 31 105 AH engine start batteries, with Victron 200 Amp Charger
- LED navigation and anchoring lights
- Bonded electrical system and underwater fittings

### PLUMBING

- Two automatic bilge pumps
- Dometic MasterFlush 8112 head w/25 gal. holding tank, marina pump out & overboard macerator discharge
- Gray water sump w/strainer and clear inspection port for shower, icebox and any AC condensate
- 8 Gallon Hot Water Tank (w/ Shorepower)
- On-demand fresh water pressure system
- Scandvik hot/cold transom shower

NOTICE: These Specifications of design, equipment, layout and construction are subject to change without notice or MJM being obligated to incorporate such changes in boats under construction or previous products. Estimated weights, speeds, fuel consumption and other performance characteristics may vary based on options selected.